

CE	Instruction Manual / 使用手冊	F - □□
	Infrared beam sensor / 自動門安全感測器	A-11+SC-6M series
For Automatic door safety		

- * 「Push-in」 fixed method
- * Immune to sunlight
- * Dark ON/ light ON changeable
- * Off delay time : 0.5 sec

◆ Specification / 基本規格

Product	產品	Amplifier		Sensor head
Model	型號	A-11-110V	A-11-220V	SC-6M
Power supply	工作電壓	110VAC 50/60Hz	220VAC 50/60Hz	<p>* Fixed hole : 12.5Φ±0.2</p>
Current consumption	耗電流	3VA Max.		
Response time	反應時間	5 ms max.		
Min. sensible object	最小檢測物	10.0Φ Opaque object		
Control output	控制輸出	1a / Relay (3A/250VAC)		
Output status	輸出狀態	NO/NC changeable		
Off delay	復歸延遲	0.5s		
Operating circumstance	工作環境	- 20℃ ~ +80℃ ; 35% ~ 85% RH		

◆ Connection diagram 接線圖

Bk2	Bk1	Br	Bl	Bl2	Br2	Bl1	Br1
5	6	7	8	9	10	11	12
Receiver				Emitter			
A-11							
Power				Output			
1	2			3	4		
~	~			Com	NO		

「Br」: Brown wire 「Bl」: Blue wire
「Bk」: Black wire

◆ Outline dimension 外形尺寸

